L..clean

L clean creates "cleanness"...



⋖Usage example in a hospital 1-spot faucets for the ozone water use.

Usage example in a supermarket ▶ 3-spot faucets for the ozone water use. 1-spot faucet for the floor wash handgun use.



Change tap water into ozone water.

L clean is unique and only one generator that can offer stable ozone water at a moderate price.

■optional related products





Dimension W300×D200×H350mm Front view. Side view About 11kg 30W(AC100V) Spitting ozone water amount 5.5~16.5L/min Amount of generating ozone 1.2g/h Ozone water density. (aprox) About 0.8~About 1.2ppm ←200mm→ TT-15MDS

Patented It can play a double role (High density oxygen water and ozone water)



JUN-KI-SUI TMO-05 VEGA Jr TMB-3GNK

High density oxygen water 5L/min Amount of generating ozone 0.6ppm Ozone gas function 0.8g/h 高濃度酸素水濃度 20ppm

Patented Ozone water by Tornado method Patented Rotary P.S.A Built-n digital UV ozone monitor Density stabilizing function (Regulator function)
Remote control Ag+silver ion function



NEW VEGA TMO-25NA

Ozone water density 1.0~1.5ppm
Amount of generating ozone 3.0g/h
Ozone gas function

Ozone water density 0.6~2.5ppm
Amount of generating ozone 3.0g/h
Ozone gas function

DoMo

Digital ozone density monitor Built-in self suction pump (patent pending) and digital display allows anyone to measure ozone density easily.



Main specifications


Measurement density range 0.00∼4.99mg/L Measurement precision ±1%FS Dimension 200W×136D×185H



L.clean

Disinfects and deodorizes by using power of ozone. More Human&Environmental-friendly More enhanced performance For more people More convenient







Approved products for administrative innovation plan in the year 2006 and 2007. NO 1048-205

Specifications and designs of these products are subject to change without notice beforehand. 06.12 L-003